

TITGEMEYER[®] GTO

YOUR SOLUTION

■ Pull-Link[®] PB50 battery-operated blind rivet tool



Pull-Link® PB50 battery-operated blind rivet tool

Pull-Link® PB50 – get started with battery technology

The PB50 is exceptional value for money and stands out for its performance, fast operation speed and operational safety. With its ergonomic design, this tool is effortless to use and flexible, with no cords tying you to a specific workstation. Its lithium-ion battery technology is capable of handling up to 600 installation processes per battery charge. The tool comes supplied in a high-quality storage case comprising nose pieces, a charger as well as a 1.4 Ah insertable battery.

A 2.8 Ah insertable battery is optionally available. The Pull-Link PB50 battery-operated blind rivet tool installs standard 2.4 mm – 5.0 mm blind rivets made of any material.

Overview

- Exceptionally good balance of weight, size and performance
- Fast installation speed
- Long battery life per charge: up to 600 installation processes per charge (standard 4.8 mm steel/steel blind rivets; 1.4 Ah insertable battery)
- Lithium-ion battery technology

Range of application

Standard 2.4 mm – 5.0 mm blind rivets made of any material

Technical specifications

Stroke:	20 mm
Insertion force:	10 kN
Motor:	14.4 V DC motor
Length:	285.5 mm
Height:	273 mm
Weight:	2.05 kg with battery

Scope of delivery

Pull-Link PB50 battery-operated blind rivet tool

1 x 14.4 V / 1.4 Ah insertable battery

1 x 14.4 V charger

Nose pieces 2.4 mm, 3.0 mm – 3.2 mm, 4.0 mm and 4.8 mm – 5.0 mm

Operating instructions Storage case

Part No. 329 050 000



Pull-Link® PB50 battery-operated blind rivet tool

Range of application

For standard 2.4 mm – 5.0 mm blind rivets made of any material. Installation force: 10 kN.

Battery status display

Optical battery charge display.



Ergonomic design

For effortless, flexible installation work.

Li-ion insertable battery

No memory effect.
For up to 600 installation processes.

Specifications

Blind rivet type	Material				
	Al/St	Al/Va	Al/Al	St/St	Va/Va
Standard POP and TIFAS up to 4.8 / 5.0 mm	•	•	•	•	•

Spare parts

Description	Part No.
Nose piece 2.4 mm	329 050 101
Nose piece 3.0 – 3.2 mm	329 050 102
Nose piece 4.0 mm	329 050 103
Nose piece 4.8 – 5.0 mm	329 050 104
Jaws	329 050 105
Jaw case	329 050 106

Batteries and charger

Description	Part No.
1.4 Ah Li-Ion PB50 battery	329 050 900
2.8 Ah Li-Ion PB50 battery	329 050 901
PB50 charger	329 050 910



■ **Gebr. TITGEMEYER GmbH & Co. KG**

■ Hannoversche Straße 97

■ (Navigation: Hettlicher Masch 2)

49084 Osnabrück, Germany

P.O. Box 43 20

49033 Osnabrück, Germany

Phone: +49 (0)5 41/58 22-0

Fax: +49 (0)5 41/58 22-491

email: fasteners@titgemeyer.com

www.titgemeyer.com